

# **SUB 15-AX**

# PROFESSIONAL ACTIVE 15" SUBWOOFER



## Description

The SUB 15-AX is a portable 15" high-power active subwoofer for live sound applications with fully featured processing, a color touch panel, and remote control via Bluetooth®. The combination of a latest-generation transducer with a powerful Class-D amplifier delivers sound pressure levels up to 133 dB with exceptional clarity and headroom. SUB AX subwoofers are designed specifically for small to mid-sized venues and ideal for portable applications. SUB 15-AX is the ideal complement for 10" or 12" woofer-size loudspeakers; it centralizes speaker management inside the subwoofer, providing dual crossovers, 8-band EQs, routing, delays, cardioid configurations, and recallable crossover presets. The polyurea-coated all-wood cabinet features a sealed Powercon True1 Top connector.

### **Features**

- > 2200 Watt Class-D Amplifier
- > 133 dB MAX SPL
- > 15" Woofer, bass reflex housing
- › Digital Crossover w/ Presets
- > Multi-ply hardwood polyurea-coated
- > LiveRemote App
- > Dual XLR/TRS combo Input + Link, Dual XLR Xover Out
- > Bass Motion Control excursion management
- > Powercon True1 Top Sealed AC Connector

## Part Number


13000832 SUB 15-AX	100-120 V	Black	EAN 8024530021849
13000835 SUB 15-AX	220-240 V	Black	EAN 8024530021818
13000877 SUB 15-AX W	100-120 V	White	EAN 8024530021894
13000878 SUB 15-AX W	220-240 V	White	EAN 8024530022044




# **SUB 15-AX**

# PROFESSIONAL ACTIVE 15" SUBWOOFER

## Line Art 2D





35 Hz ÷ 120 Hz

-2 dBu/+4 dBu

133 dB

#### **TECHNICAL SPECIFICATIONS**

**Acoustical specifications** 

Frequency Response Max SPL @ 1m

**Transducers** 

1 x 15", 3.0" v.c Woofer

Input/Output section

bal/unbal Input signal Input connectors Combo XLR/Jack

Input sensitivity

Output connectors XLR

**Processor section** 

Protections Thermal Limiter Soft Limiter

Controls

Encoder for Volume control and data entry. Touch Screen for

parameter management and monitor.

Power section

Size

2200 W Peak, 1100 W RMS **Total Power** 

Cooling Convection

Connections Powercon TRUE1 TOP IN/OUT

Standard compliance **Physical specifications** 

Safety agency CE compliant Plywood Cabinet/Case Material

Handles 1 handle per side Yes

Pole mount/Cap Grille Steel Black, White

Color

590 mm / 23.23 inches Height Width 420 mm / 16.54 inches Depth 590 mm / 23.23 inches Weight 31.4 kg / 69.23 lbs

**ACCESSORIES** 

**Protections** Rigging / Mounting CVR 004 13360529 8024530020415 Black 8024530022303 PM-KIT M20 13360638 White PM-KIT M20 13360067 Black 8024530014599

**Technical Specifications** Page 2 of 2